

Management of off-site Waste Contaminated with Radioactive Materials due to the Accident at Fukushima Nuclear Power Stations


Nov. 28, 2012

Ministry of the Environment, Japan

1. Current Situations

- 2. Countermeasures
 - 1) Act on Special Measures concerning the Handling of Radioactive Pollution
 - 2) Designated waste
 - 3) Waste in the Countermeasure Area
 - 4) Recycle of waste
 - 5) Interim Storage Facility
- 3. Conclusions and Challenges

Radiation level map in Eastern Japan and the disposal of disaster waste



Major detected radioactive materials: Cs 134, Cs137

1. Current Situations

2. Countermeasures

- 1) Act on Special Measures concerning the Handling of Radioactive Pollution
- 2) Designated waste
- 3) Waste in the Countermeasure Area
- 4) Recycle of waste
- 5) Interim Storage Facility

3. Conclusions and Challenges

Outlines of the Act on Special Measures*

*The Act on Special Measures concerning the Handling of Environmental Pollution by Radioactive Materials Discharged by the Nuclear Power Station Accident Associated with the Tohoku District – Off the Pacific Ocean Earthquake that Occurred on March 11,2011

Purpose

To promptly reduce the impacts of environmental pollution by instituting measures taken by interested parties, especially ,the national and local governments and the relevant licensee of NPP (i.e. Tokyo Electric Power Company)

Roles of Interested parties

- (1) The national government:
 - <u>To implement any necessary measures in consideration of its social responsibilities</u> associated with the promotional efforts thus far channeled into its nuclear energy policy.
- (2) Local governments:
 - To carry out their proper role through cooperation with the measures by the national government.
- (3) The relevant licensee of NPP:
 - <u>To implement any necessary measures in confidence</u>, while <u>assisting the national and local governments</u>.

Basic principles formulation and others

- The Minister of the Environment <u>develop a draft of the basic principles and seek a Cabinet decision.</u>
- The Minister of the Environment <u>set standards for the processing of contaminated waste and soil</u>
- The national government <u>establish a system of unified monitoring and measurement</u>

Outlines of the Act on Special Measures concerning the Handling of Radioactive Pollution

"Management of Contaminated Waste"

Specified waste

(1) Waste within the countermeasure area

Contaminated waste in the countermeasure area designated by the Minister of the Environment



A management plan for waste within the countermeasure area is <u>formulated</u> by the Minister of the Environment



Implementation by the national government pursuant to the treatment plan for waste

(2) Designated waste

Survey on sewerage sludge, incinerated ash, etc (obligatory)

Survey on waste other than that specified in the left box (voluntary basis)

Report to the Minister of the Environment



Designation as "designated waste"
by the Minister of the Environment
* Contaminated Waste above certain level



Implementation by the national government

Prohibition on unauthorized actions (ex. Unauthorized dumping)

Low-level contaminated waste other than specified waste


Measures to be taken in accordance with the Waste Management Act

Basic Approach of Waste Disposal Contaminated by Radioactive Materials

"Near –term policy to ensure the safety for treating and disposing contaminated waste around the site of Fukushima Dai-ichi Nuclear Power Station of Tokyo Electric Power Company" by Nuclear Safety Commission (June 3, 2011)

- Radiation expose of the residents living in the vicinity of the facilities during the treatment of contaminated materials: under 1mSv/y
- Radiation expose of the residents living in the vicinity of the facilities after termination of institutional control: under 10µSv/
- Management of disaster waste contaminated by radioactive materials was designed to correspond with this near-term policy.

Outline of exposure scenario considered waste management



Result of safety evaluation derived from Scenario

		Target for	Radioactivity concentration resulting					
Scenario		Evaluation	in an exposure dose of 1mSv/y					
Storage	Waste loading and unloading work	Workers (1000h/y)	12,000 Bq/kg					
	Those living around storage sites	Public (Outside in	100,000 Bq/kg					
		20% resident time)	*A certain distance from a storage					
Transfer	Waste transfer work	Workers (1000h/y)	10,000 Bq/kg					
	Those living around transfer routes	Public (450 h/y)	160,000 Bq/kg					
Incineration	Incinerator repair work	Workers (900h/y)	30,000 Bq/kg					
	Those living around incineration	Public (Outside in	5,500,000 Bq/kg					
	facilities	205 resident time)	Operational period —					
Landfill	Incineration ash landfill operations	Workers (1000h/y)	10,000 Bq/kg					
	Dewatered sludge, etc. landfill	Workers (1000h/y)	8,000 Bq/kg					
	operations		←					
	Those living nearby the final	Public (Outside in	100,000 Bq/kg					
	disposal site	20% resident time)	*A certain distance from a landfill					
	Use of the landfill site as a park	Public (200h/y)	170,000 Bq/kg					
			*exposure dose of 10 μSv/y					
	Ingestion of crops grown with	Public	46,000 Bq/kg					
	underground water		*exposure dose of 10 μSv/y					

Landfill Disposal of Incinerated Ash According to the Act on Special Measures Concerning Management of Radioactive Contamination

	8,000 Bq/kg	or under				
	Other (Criteria of Waste Management Act)	Specified Domestic Waste & Specified Industrial Waste ^{**2}	8,000~100,000 Bq/kg	Exceeding 100,000 Bq/kg		
Structure of landfill site	· ·	oe landfill site ^{※1} (Landfill I work and drainage treatr	• • •	Isolated type landfill site (Landfill site equipped outer intercept)		
Preventive measures against leaching of radioactive material	None	-*Installing the soil layer *-Prevention of rainwater penetration into fly ash	*-Cement solidification -*Installing the soil layer *-Establishing the impermeable soil layer	None (No Leaching of Radioactive Material due to Water Blocking)		
Monitoring of radioactive material	None	*Discharged water *Groundwater *Air dose rate in the v	ricinity	*(Non-existence of discharged water) *Groundwater *Air dose rate in the vicinity		

^{*1} Isolated type of landfill site is possible to be used.

 $^{*^2}$ Incinerated ash, sewerage sludge, etc, generated from areas with possible contamination with accident-origin radioactive materials near 8,000 Bq/kg.

1. Current Situations

2. Countermeasures

- 1) Act on Special Measures concerning the Handling of Radioactive Pollution
- 2) Designated waste
- 3) Waste in the Countermeasure Area
- 4) Recycle of waste
- 5) Interim Storage Facility

3. Conclusions and Challenges

Current status of Designated waste [as of November 2nd, 2012]

	Incineration Municipality solid waste	, <i>,</i>	Wasted sludge (t) (Domestic water)	Wasted sludge (t) (Industrial water)	Sewage sludge (t)	Agriculture and forestry Waste (t)	Other (t)	Total (t)
Iwate	181	0	0	0	0	0	176	358
Miyagi	0	0.2	1011	0	0	2238	0	3250
Yamagata	0	0	0	0	0	0	2.7	2.7
Fukushima	57,676	1,474	1,639	168	8,589	30	307	69,883
Gunma	0	0	451	127	171	0	0	749
Tochigi	1,034	0	585	0	2,200	3,535	0	7,354
Ibaraki	1,763	0	0	0	926	0	0	2,689
Chiba	1,592	0.6	0	0	0	0	0	1,592
Tokyo	981	1	0	0	0	0	0	982
Niigata	0	0	1,018	0	0	0	0	1,018
Shizuoka	0	0	0	0	0	0	8.6	8.6
Total	63,227	1,476	4,704	295	11,886	5,803	328	87,884

Policy of disposal of designated waste (March 30, 2012), and Image of Landfill Disposal of Designated Waste

- National Government keeps effort to manage designated waste, which should be disposed of in each prefecture. If possible, the existing landfill site would be utilized for those waste.
- National Government determines sites from a few candidate sites when a landfill site is newly constructed.
- National Government lessens a burden of storage of agricultural by-products by intermediate treatment such as incineration, drying, and melting.





Image of Landfill Disposal of Designated Waste

The period after landfill with monitoring and maintenance



1. Current Situations

2. Countermeasures

- 1) Act on Special Measures concerning the Handling of Radioactive Pollution
- 2) Designated waste
- 3) Waste in the Countermeasure Area
- 4) Recycle of waste
- 5) Interim Storage Facility

3. Conclusions and Challenges

Countermeasure Area

Naraha-Town, Tomioka-Town,
Okuma-Town, Futaba-Town,
Namie-Town, Katsurao-Village,
Iidate-Village, Tamura-City,
Minamisouma-City, Kawamata-Town,
Kawauchi-Village


Area 1: <20mSv/yr

Evacuation orders are ready to be lifted

Area 2: 20 – 50 mSv/yr
Areas in which residents are not permitted to live

Area3: >50 mSv/yr
Residents will face difficulties in returning for a long time

No-entry zone:



Amount of waste in Countermeasure Area (June, 2012)

	Estimate amound disaster waste [t		Activity concentration of Cs [Bq/kg]	Estimated Area of temporary	
	Sum		nbustible waste ombustible waste	storage sites [m ²]	
Minamisoma City	183,000	74,000 109,000	2,800 200	111,000	
Namie Town	178,000	46,000 132,000	1,300 200	103,000	
Futaba Town	12,000	5,000 7,000	9,700 900	11,000	
Okuma Town	29,000	17,000 12,000	58,700 11,600	18,000	
Tomioka Town	47,000	17,000 30,000	11,500 1,100	27,000	
Naraha Town	25,000	10,000 15,000	3,500 1,000	21,000	
Sum	474,000	169,000 305,000	-	291,000	

Disposal of waste in the Countermeasure Area

- Waste disposal plan in the countermeasure area was released in June 11, 2012.
- Temporary storage sites are being selected now with the cooperation of municipalities.
- It is effective to set two temporary incineration plants in the area. However, if each municipality can prepare sites for temporary incineration plants and waste can be treated smoothly, National Government thinks of the setting of temporary incineration plants in each municipality.
- An existing private controlled type landfill site will be used for disposal of waste in the countermeasure area and designated waste in Fukushima, whose activity concentration is 100,000 Bq/kg or under than 100,000 Bq/kg.

1. Current Situations

2. Countermeasures

- 1) Act on Special Measures concerning the Handling of Radioactive Pollution
- 2) Designated waste
- 3) Waste in the Countermeasure Area
- 4) Recycle of waste
- 5) Interim Storage Facility


3. Conclusions and Challenges

Idea of recycle of disaster waste with control in Fukushima Prefecture (December 27, 2011)

- According to "Near –term policy to ensure the safety for treating and disposing contaminated waste around the site of Fukushima Dai-ichi Nuclear Power Station of Tokyo Electric Power Company" by Nuclear Safety Commission (June 3, 2011), it is necessary to check that the activity concentration is controlled as lower than 10 μ Sv/y before the recycled materials are put on the market.
- Incombustible disaster waste such as concrete debris can be used as materials for recovery such as base course material along with the policy.
- Exposure scenarios of recycle are set.

Idea of recycle of disaster waste with control in Fukushima Prefecture (December 27, 2011)

- The most critical scenario is living nearby road.
- When 30 cm thick shield materials exist, under than about 3,000 Bq/kg disaster waste can be used.
- When thicker shield materials exist, higher activity concentration of disaster waste can be used.
- After the construction, it is necessary to keep the thickness of shield materials.
- Projects to adapt to this idea are fundamentally limited to public projects.
- An administrator should records of sites, amount, activity concentration of disaster waste recycled.



1. Current Situations


2. Countermeasures

- 1) Act on Special Measures concerning the Handling of Radioactive Pollution
- 2) Designated waste
- 3) Waste in the Countermeasure Area
- 4) Recycle of waste
- 5) Interim Storage Facility

3. Conclusions and Challenges


Decontamination Plan Overview

- Decontamination of the radiation-contaminated environment caused by the accident of Fukushima 1st Nuclear Power Station
- Removed soil and other wastes decontaminated are temporary stored on site, converged to Interim Storage Facility (ISF), then transferred to final disposal site outside Fukushima.
- Interim Storage Facility (ISF): To ensure safety and provide intensive control of the radiation materials (soil and waste) till the final disposal site is available



Decontaminated Soil and waste: Flow chart

Decontaminated soil and wastes amount to over 30million_m³ in maximum.
 Require ISF to be approx. 28million_m³ capacity in maximum.




ISF: Storage Facility Image

- Several types of Storage Facilities may be installed according to the characteristics of stored soil and waste.
 - Level of contamination
 - ✓ Leachate traits under various environmental scenario.


Example of facilities for radioactive waste which can generate leachate

Example of facilities for radioactive waste which does not generate leachate



ISF: Bird-view Image

- Total storage volume ranges 15-28 million_m³ according to the decontamination scope and methods
- Should contribute to municipal economy during construction and monitoring phases.






* The image is conceptual. Actual facilities and their layouts will be modified to the sites selected.

ISF: Facility Components

- Waste Emplacement and Segregation Facility
 - Confirmation of waste characteristics (weights, surface dose rate etc.)
 - ✓ Segregate waste into combustibles or non-combustibles, radioactive or not.
- Storage Facility
 - ✓ Store soil and waste, prevent radiation from leaking and water contamination
- Waste Volume Reduction Facility
 - Incineration plant with associated facilities
 - Other volume reduction facilities
- Monitoring Centre
 - Continuous monitoring of storage sites (stored soil and waste) and surrounding environment (e.g. air, ground water).
- Research and Development Centre
 - R and D for volume reduction technology for stored soil and waste, and for high concentration isolation technology, etc.
- Public Information Centre


Transportation Plan

- Divide into 3 areas corresponding to ISF locations (FUTABA, OKUMA and NARAHA).
- Challenge: Mgmt. of huge volume transportation, avoiding local congestion.



Potential Construction Sites

- 12 potential sites (for preliminary survey) around the Fukushima 1st and 2nd nuclear power plants
 - Vicinity to the highly contaminated (=high volume) area
 - Sufficient area for storage and related facilities
 - Transportation conditions (mitigation of congestion etc.)
 - Avoid of active fault and soft ground
 - Minimization of surface water diversion



Major Events

Oct. 2011 The Ministry of the Environment announced the basic plan of ISF; explain to the heads of relevant municipalities.

Dec.2011 The Minister requested 8towns in Futaba county and Fukushima Pref. to examine potential location in Futaba county.

Mar.2012 The Minister explained 8 towns and Fukushima Pref. that facilities be dispersed in three towns (Futaba, Okuma and Naraha)

Aug.2012 The Minister requested 8 towns and Fukushima Pref. that feasibility surveys be implemented in Futaba County

Overall Schedule

=				_	_	_		_	_	_	_	_	_	_	_	_	_	_	_	_	_	_		_	
No			FY2011 FY2012 FY2013 FY2014 FY2015 and beyond																						
-	ltem	Det	ails	4	7	10	1 4	1 7	10	1	4	7	10	1	4	7	10	1	4	7	10	1	1		Notes
1	Survey on basic concept	● Investigate type, condition ar as well as concentration of rad ● Rough estimate of cost of fa contruction costs, investigate p sites)	lioactive materials cility structure, scale and				ept survey)			-				по поставления поставления с п										
2	Selection of site for interim storage facility	●Coordination with prefect of selected site for interim s					Coordinat	tion with	prefect or locality	ure,							THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAMED IN COLUMN TWI								
3	Basic design, execution design	● Rough estimate of cost of st for interimstorage facility *Bas preliminary discussions), execuproject and acqiusition of land)	sic design(outline for various ution design(for contracting of					Bas des		E	ecutio	n des	ign	\rangle											
4	Environmental impact assessment, impact study of radioactive materials on the environment	● Study, assessment and s on environmental impact ● Study on environmental ir measures for radioactive m	mpact, assessment, and					Docu rese	ment		Fields	tudy	\supset											1	
5	Site acquisition	●Land survey for site acq ●Site acquisition for inter									Survey		Site acquis				Water and the Control of the Control)	
6	Processing of various types of permits for development	●Consultation on develop land, forest, urban area, no cultural property etc.)						Preli	minary		Main co (held a														
7	Construction of roads etc. for construction site	●Construction of roads, to	emporary facilities etc.													-									
8	Main construction of interim storage facilities	●Implementation of main storage facilities	construction of interim																			***************************************	$\left\langle \right\rangle$	$\langle \rangle$	
9	Installation of wastes etc.	●Installation of wastes et	с.														ĺ	Insta sta	allatio rting v	n carr with c	ied ou omple	ıtin or eted si	der, tes		
	Surve	y of use of existing dispo	osal sites				l	J	· · · · ·	l	II				<u> </u>				l					$\langle \cdot \rangle$	
		Decontamination				Monitori	ng. ng	b) (esp	munici ecially o	palities outside (espe	lation in s and n e highly ecially areas	ationa conta high	l gover minate	rnmen ed area	t	mination hly		Beg			tion to	o inte	rim		Even after the initial major decontamination, it is expected that long term, supplimental decontamination will be needed to deal with natural pollutant movement. Nevertheless, the national government will complete final disposal outside Fukushima prefecture within 30 years starting from the beginning of installation into interim storage. For final disposal, much will depend on advances in technology to effectively isolate and condence radioactive materials and so the national government will make efforts in research development and evaluation of technology
	Disposa	al of wastes	Wastes fromareas under measures			Plann Installati temporar	on into	Dispo	sal in e	xisting	of high	f low I	evel ra	dioact	tive mat	terial						rage faci			Wastes from areas under measures will be disposed of in order from FY2011
Designated wastes						designa design was	ated >				of high sites of	_)B	egin ins	stallation	to inte	rim sto	rage faci	iities//	3	 Designated wastes will be designated in order and disposed of as generated
For decontamination, installation into interim storage facilities will start after 3 years from beginning of the installation into temporary facilities.																									

1. Current Situations

2. Countermeasures

- 1) Act on Special Measures concerning the Handling of Radioactive Pollution
- 2) Designated waste
- 3) Waste in the Countermeasure Area
- 4) Interim Storage Facility

3. Conclusions and Challenges

Conclusions and Challenges

- Waste management began last year in parallel with development of framework.
- Technical challenges
 relatively highly contaminated waste disposal including
 incineration
- Siting challenges temporary, interim storage and landfill site etc.
- Communication challenges
 trust building, knowledge base for people, especially neighborhood of facilities etc.